



**dBA UL-Cork**

Floor Underlay

**Description**

dBA UL-Cork is an agglomerated cork and recycled rubber underlay for impact noise and thermal floor insulation. This underlay consists in a homogenous material produced from cork and recycled rubber granules which can be placed under different flooring solutions to improve its sound insulation levels.

**Specifications**

Material:  
**Cork and Recycled Rubber**

Dimensions:  
**15000 x 1000 x 3 (mm)**

Installation:  
**Chemical**

**Technical Information**

	<b>Value</b>	<b>Standard</b>
<b>Roll Dimensions [mm]</b>	15000 x 1000	-
<b>Thickness [mm]</b>	3	-
<b>Density [kg/m³]</b>	600 -700	ISO 7322
<b>Tensile Strength [kPa]</b>	> 800	ISO 7322
<b>Compression at 0,7 MPa [%]</b>	15	ISO 7322

**Applications**



**Acoustic Performance**

<b>Flooring</b>	<b>Impact Sound Reduction Index (<math>\Delta L_w</math>)* [dB]</b>
Laminate	19
Glued Down Wood	16
Ceramic / Natural Stone	16
LVT	19

\*  $\Delta L_w$  measured with *UL-Cork* applied directly under the flooring and over a 140 mm concrete slab.



hello@artnovion.com  
www.artnovion.com